



Bullbone 97 x 25 mm M830

The Bullbone M830 label from RICHRFID is designed for global supply chain, logistics, and industrial applications.

It delivers stable, high-performance RFID operation even in harsh environments and on a wide range of material surfaces.

The product is complied with EPC global Class 1 Gen 2, ISO 9001 quality management and ISO 14001 environmental management standards, ensuring reliable, industry-grade performance for diverse use cases.

Equipped with the Impinj M830 IC. The IC has an improved read / write sensitivity compared to the M700 series, enables faster, more accurate bulk reading performance. The Impinj IC is compatible with the global GS1 UHF Gen2v2 standard, which ISO/IEC standardized as 18000-63.

The Antenna size 94 x 22 mm is optimized for long-range, ideal for factory inbound / outbound processes, RTI management and inventory management.

The label size 97 x 25 mm provides ample space for QR, serial numbers, and other readable information, supporting on-site visual verification.

Overview


Frequency Band
UHF 860-960 MHz

Chip Type
Impinj Monza 830

Dimensions
97 x 25 mm / 3.82 x 0.984 in

Air Interface Protocol
ISO/IEC 18000-63 Type C


Application
Supply Chain
Logistics
Industry & Manufacturing
Healthcare & Pharmaceuticals






Model	RC5129
RFID Features	
Frequency	860-960 MHz
Application	Non metal
Chip Type	Impinj Monza 830
Memory	User - N/A; EPC - 128 bits; TID - 96 bits
Data Storage	> 10 years
Re-write	100,000 times
Physical Features	
Dimensions	97 x 25 mm / 3.82 x 0.984 in
Material	Coated Paper
Adhesive	Hot Melt
Operating Temperature	-40°C to 85°C / -40°F to 185°F
Storage Condition	20±5°C, 50±10% RH, Store away from sunlight
Other Features	
Installation	Adhesive on clean & dry surface
Customization	Printing, Encoding, Designing, etc.
Package	2,500 pcs / roll, 4 rolls / box

Read Range(2W ERP)



Radiation Pattern



PS: The performance is theoretical values in the lab and the actual effect depends on the specific applications.

RICHRFID

Web: <https://www.richrfid.com> E-mail: info@richrfid.com
Shenzhen | Hong Kong | Singapore | Seoul | Tokyo | Paris



DISCLAIMER

All specifications are indicative and results may vary. Each user bears full responsibility for making its own determination as to the suitability of RICHRFID products, materials, services, recommendations, or advice for its own particular use.

For intended use only. Not to be repurposed or used for other applications without prior written permission from the manufacturer.

@2026 RICHRFID. All rights reserved.